



Main Features

- Functions: Amplifier, DAC, Network, CD, USB Memory, Bluetooth®
- Flagship Hi-Res CD Receiver with Network Accessibility
- Full-stage Dual Monaural Differential Circuit Design
- L/R Channel Individual Dual AK4490 D/A Converters
- Center-mounted Drawer-type CD Drive engineered by TEAC
- OpenHome for NAS Music Server Access
- Internet Music Streaming Access at Flat Fee* (TIDAL, qobuz, MQA** and roon***)
- Bluetooth® Wireless Music Streaming from Smartphone/Tablet
- LDAC, aptX®, and AAC High-quality Codec for Bluetooth®
- DSD Direct Input to Coaxial/Optical Inputs (DoP 2.8MHz format)
- RDOT NEO Up-conversion to DSD 12.2MHz/PCM384kHz
- Dual Master Clocks for 44.1kHz and 48kHz Systems
- AMAC (Aluminum-Block Mounted Amplifier Construction) for
- Effective Heat Exhaust and Simplified Signal Paths
- Individually Coiled EI-core Power Supply and Shunt Regulator
- Classical VU Meters with Dimmable Backlight
- High-contrast OLED Information Window with Dimmable Backlight
- Machined Aluminum Volume Knob with Precision Ball-bearing Axis
- Aluminum Body and Dual-layered Metal Chassis
- "TEAC-OVCS" Octa Volume Control System
- 4-polar Headphone Jack supporting Ground Separate Mode
- 3 Patent-registered Pin-point Feet for Stable and Easy Installation
- A3-size Footprint
- Wide-pitch Gold-plated Machined RCA Connectors accommodate
- Pin Cable with Extra large shell
- Free iOS/Android-based Control Apps "TEAC HR Streamer" available
 - * Available in limited countries due to copyrights and licensing issues.
 - ** Available from June.
 - *** Available from July.

General Specifications (US ver.)

- Max Output Power: 210W+210W (4ohms, 1kHz, THD 10%)
130W+130W (8ohms, 1kHz, THD 10%)
- Rated Output Power: 110W+110W (4ohms, 1kHz, THD 0.07%)
60W+60W (8ohms, 1kHz, THD 0.07%)
- T.H.D 0.008% (1kHz, 8 ohms, 50W)
- S/N Ratio: 110dB (LINE IN, IHF-A/LPF 20kHz 1kHz 2V)
- Frequency Response: 5Hz - 100kHz (+1dB/-3dB)
- Headphone Output: 500mW+500mW (at 32ohms loaded)
- Supported CD: CD-DA, CD-R/RW
- Digital Input Formats:
 - Coax/Optical: DoP 2.8MHz, PCM 192kHz/24bit
 - LAN/USB: DSD 5.6MHz (DSF, DSDIFF), PCM 44.1k - 384kHz/32bit (FLAC, ALAC, WAV, AIFF, MP3, AAC)
- Bluetooth® Version: Version 4.0, Class2
- Bluetooth® Codec: LDAC, aptX®, AAC, SBC
- Analog Audio Input: x1 (RCA Pin)
- Digital Audio Input:
 - Coaxial: x1 (RCA Pin)
 - Optical: x2 (TOS-link)
 - USB Port: x1 (USB A-type, USB2.0)
- Network: 1000BASE-T
- Headphone Output: x1 (3.5mm 4-polar)
- Speaker Terminals: x1 set (Large Screw-type, Gold-plated)
- Operation Power: AC 120V 60Hz (US version)
- Dimensions (W x H x D): 17.4" x 6.0" x 13.6"
442 x 152 x 345 mm
- Weight: 29.6 lbs. 13.4 kg