



K-01X



K-03X



RC-1315 (K-01X)



RC-1301 (K-03X)

Compatible Disc Types (Playback)

Super Audio CD, CD (including CD-R and CD-RW)

Analog Audio Outputs

Connectors XLR connector (2ch) × 1; RCA connector (2ch) × 1

Output impedance XLR: 40Ω; RCA: 10Ω

Maximum output level (1kHz, full-scale, into 10kΩ)
XLR: 4.8Vrms RCA: 2.4Vrms

*Output level drops 3dB for DSD data playback when DSD Filter is off.

Frequency response** 5Hz to 40kHz (-3dB)

S/N ratio** K-01X: 117dB; K-03X: 116dB

Total harmonic distortion** K-01X: 0.0006% (1kHz); K-03X: 0.001% (1kHz)

**Super Audio CD, XLR analog output

Digital Audio Output

XLR connector × 1 3 Vp-p (into 110Ω)

RCA connector × 1 0.5 Vp-p (into 75Ω)

Digital Audio Input

RCA connector × 1 (input impedance 75Ω)
0.5 Vp-p

Optical digital connector × 1 -24.0 to -14.5dBm peak

USB-B connector USB 2.0 standard

Clock Sync Input Format

Connector BNC

Supported input frequencies (±15ppm)

44.1, 48, 88.2, 96, 176.4, 192kHz,
10, 22.5792, 24.576MHz

Input impedance 75Ω

Input level Rectangle wave: equivalent to TTL levels;
Sine wave: 0.5 to 1.0 Vrms (50 to 75Ω)

General

Power supply AC 230V, 50Hz; AC 120V, 60Hz; AC 220V, 60Hz

Power consumption K-01X: 27W; K-03X: 25W

External dimensions

(W x H x D, including protrusions)
445 × 162 × 438mm (17 1/4 × 6 3/8 × 13 1/4 in)

Weight K-01X: 31kg (68 3/8 lbs); K-03X: 28kg (61 3/4 lbs)

Included accessories

Power cord set × 1; Remote control (K-01X: RC-1315; K-03X: RC-1301) × 1;

Batteries for remote control (AAA) × 2; Felt pads × 3;

Owner's manual × 1; Warranty card × 1



K-01X / K-03X